

Material Lifts

Super Hoist™

Specifications

Models	GH™-3.8		GH-5.6	
Measurements	US	Metric	US	Metric
A Height - stowed	3 ft 5 in	1.04 m	4 ft 6 in	1.37 m
- lifting height	12 ft 5.6 in	3.80 m	18 ft 4.5 in	5.60 m
B Length - platform	1 ft 5 in	.43 m	1 ft 5 in	.43 m
C Width - platform	2 ft	.61 m	2 ft	.61 m
D - base (corner to corner)	4 ft 5 in	1.35 m	4 ft 5 in	1.35 m

Productivity


Load capacity	300 lbs	136 kg	250 lbs	113 kg
Storage/transport dimensions	14x14x39.5 in	.36x.36x1 m	14x14x39.5 in	.36x.36x1 m

Power

Recommended PSI	85 psi	5.86 bar	85 psi	5.86 bar
-----------------	--------	----------	--------	----------

Weight*

	75 lbs	34 kg	82 lbs	37 kg
--	--------	-------	--------	-------



* Weight will vary depending on options and/or country standards.

Features

Standard Features

Measurements

GH™-3.8

- 12 ft 5.6 in (3.80 m) lifting height
- 300 lbs (136 kg) load capacity

GH-5.6

- 18 ft 4.5 in (5.60 m) lifting height
- 250 lbs (113 kg) load capacity

Productivity

- Portable and compact design
- Up and down dump valve can be easily activated by patented control handle
- Quick setup requires no tools
- The one-piece platform attaches to cylinder with a twist of the wrist
- Legs fold up and lock for easy storage
- Caster brakes
- Auto-lubricating oil reservoir on top of each piston inside the cylinder
- Easy to service
- One-piece platform

Power

- Powered by CO₂ or compressed air
- One size fits all CO₂ bottle mounting bracket

Options & Accessories

Productivity

- Platform cradle package

Power

- 20 lbs (9 kg) CO₂ tank, brushed aluminum



Genie United States

6464 185th Ave. NE
Redmond, WA 98052
Telephone +1 (425) 881-1800
Toll Free in USA/Canada +1 (800)-536-1800
Fax +1 (425) 883-3475

Distributed By:

Effective Date: November, 2018. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Terex, Genie and AWP are registered trademarks of Terex Corporation or its subsidiaries. © 2018 Terex Corporation.